

Surface Mounted Sliding Door Trim

Surface mounted turnknob and emergency release assemblies are available for use with SL1, SL2, SL5, and SL6 sliding lock systems, when recessed trim is not required. Frascio offers a wide variety of designs and configurations shown below.

Turnknob Design Options



M61 Round
Smooth Rose



M61-T Round
Traditional Rose



M61-O Round
Octagonal Rose



M61-Q Round
Square Rose



RM61-Q
Rectangular
Square Rose



A51 Oval



H41
Accessibility



R71
Accessibility



R71-Q
Accessibility
Square Rose

Emergency Release/Indicator Options



EMT



EMTI
with color
indicator window



EMTI-VO
with VAC/OCC
indicator window



EMT-Q



EMTI-Q
with color
indicator window



EMTI-Q-VO
with VAC/OCC
indicator window



GVRO
occupancy
indicator



GVRO-Q
Square
occupancy
indicator

*CF Concealed Fastener option available on round roses

Additional options and custom design capabilities are available upon request.

How to Order: Refer to the applicable **How to Specify and Order** guide for each Frascio sliding door lock system.



BDS-1 Sliding Door Wall Strike

The BDS -1 is a durable self-enclosed wall strike solution enabling sliding barn doors to lock without a door jamb or other millwork structure.

- Suitable for use with Frascio SL2 and SL5 sliding door mortise locks.
- Concealed enclosure fastener system eliminates visible screws when door is in the closed position.
- Adjustable mounting bracket provides convenient installation.

BDS-1 Specifications

Material	Stainless Steel
Standard Door Thickness	1-3/4" (45 mm)
Strike Enclosure Size	3-1/2" (91 mm) x 1-7/8" (48 mm) x 1-3/4" (44 mm)
Strike Opening Size	1-3/8" (35 mm) x 3/4" (19 mm)

